

MULTIGRADE PLUS

20W40 CF-4

Euro Multigrade Plus 20W 40 CF-4 is a heavy duty diesel engine oil. This oil is blended from selected highly refined, high viscosity index base stocks and contain well balanced group of additives, to provide high detergency, dispersancy and anti oxidation characteristics to meet the stated performance standards

Specifications :

API CF-4/SL , ACEA E2-96, MIL-L-2104 C, Caterpillar Series 3

Recommendations :

Euro Multigrade Plus 20W 40 CF-4 may be recommended for all kind of Tractors, Trucks, Buses, Generators, Diesel Engines, Cars, MUVs, SUVs etc.



Pack Sizes :

0.5, 1, 3, 5, 6, 7.5,
10, 20, 55, 210 Ltr

Main Benefits :

- Provides excellent resistance against wear and deposits in automotive supercharged diesel engines
- Has exceptional thermal and oxidation stability to resist decomposition in supercharged engines operating with high ring zone temperature.
- Provides absolute control of corrosive wear that may result from use of high sulphur fuels because of good built-in alkaline reserves.
- Maintains a high order of engine cleanliness.

PRODUCT DATA SHEET

Property	Typical Value
TBM, mg KOH / g min.	9.7
Sulphated Ash, % Wt.	1.5
Kinematic Viscosity @40°C, cSt	110
Kinematic Viscosity @100°C, cSt	14
Viscosity Index min.	136
Flash Point, (COC)*C min.	233
Pour Point C Max	-30